Core™ Compact Portable Balances

ADAM

Technical Specifications

Model	CQT 202	CQT 251	CQT 601	CQT 1501	CQT 2601	CQT 2000	CQT 5000
Maximum capacity	200g	250g	600g	1500g	2600g	2000g	5000g
Readability	0.01g	0.1g	0.1g	0.1g	0.1g	1g	1g
Repeatability (S.D.)	0.02g	0.1g	0.1g	0.1g	0.1g	1g	1g
Linearity (±)	0.02g	0.1g	0.1g	0.2g	0.2g	1g	1g
Typical stabilisation time	3 Sec	2 Sec		3 Sec			2 Sec
Draught shield dimensions	-				-		
Pan size	120mm Ø				145mm Ø		

General Specifications

Units of measurement	Kilogram (kg), Gram (g), Pound (lb), Ounce (Oz), Carat (ct), Dram (d), Grain (GN), Newton (N), Taels T. (TL.T)
Operating temperature	0°C 40°C
Power supply	12VAC 15mA
Overall dimensions (wxdxh)	173×255×86mm
Net weight	0.9kg

Key Accessories

- Security Lock and Cable
- Hard Carry Case with Lock
- In-use Cover
- In-Use Cover pack of 10
- In-Use Cover pack of 5
- M1 2kg Calibration Weight for CQT 2000
- M1 2kg Calibration Weight for CQT 5000
- F1 200g Calibration Weight for CQT 202
- M1 200g Calibration Weight for CQT 251
- M1 500g Calibration Weight for CQT 601
- M1 1kg Calibration Weight for CQT 1501

National Weights & Measures Laboratory
ISO 9001 Quality Assured Organisation
UKAS QUALITY MANAGEMENT

Adam Equipment - offices worldwide

www.adamequipment.com

Adam Equipment follows a policy of continuous improvement and reserves the right to change specifications without notice. © 20th May 2010