





Speed, Performance, Value - The Right Balance

- Non-slip adjustable levelling feet
- Approximately 3 meter long shielded cable
- Available in a range of capacities and platform sizes
- Overload protection
- Mild Steel construction
- Four load cell construction
- Uses OIML approved loadcells
- Can be supplied complete with AE402 or GK-M indicator
- Weighing
- Parts counting
- Percentage weighing
- Comparative Weighing
- Shipping and Receiving
- Batching Items for Processing
- Stock and Warehouse Auditing



Technical Specifications


Model	PT 110 + GK	PT 310 + GK	PT 112 + GK	PT 312 + GK	PT 115 + GK	PT 315 + GK	PT 310S + GK
Maximum capacity	1000kg	3000kg	1000kg	3000kg	1000kg	3000kg	3000kg
Readability	200g	500g	200g	500g	200g	500g	500g
Pan size	1000x1000mm		1200x1200mm		1500x1500mm		1000x1000mm

General Specifications

OIML Class	3
Overall dimensions (wxdxh)	1200x920x80mm
Net weight	90kg

Key Accessories

- Mild Steel Ramp - PT 12R 1200mm wide
- Mild Steel Ramp - PT 10R 1000mm wide
- Mild Steel Ramp - PT 15R 1500mm wide
- Stainless Steel Ramp - PT 10RS 1000mm wide



Adam Equipment - offices worldwide

www.adamequipment.com