

DSB4848-05

Floor Scale System



- Capacity- 2500 kg x 0.5 kg / 5000 lb x 1 lb
- Legal for Trade
 — NTEP certified at 5,000 divisions, Class III
- Versatile Indicator

 For many applications including shipping, counting, totalizing and check weighing functions
- Finish- Powder coat paint
- Load Cells
 Four alloy steel potted load cells
- RS-232

 Standard serial string with time and date
- Function— Checkweighing, count, weight, total and print
- Rugged Construction

 Thick safety tread top plate with heavy duty welded wide channel supports



DSB4848-05 Floor Scale System

DSB Specifications

Floor Scale Material:

Mild steel with 5 mm / 0.19" deck with safety tread

Capacity:

1250 kg x 0.2 kg/ 2500 lb x 0.5 lb 2500 kg x 0.5 kg / 5000 lb x 1 lb 5000 kg x 1 kg / 10,000 lb x 2 lb

Platform Dimension:

915 mm x 915 mm / 36" x 36" 1220 mm x 1220 mm / 48" x 48" 1500 mm x 1500 mm / 60" x 60"

Height Dimension: min 102 mm / 4.0"; max 118 mm / 4.6"

Finish: Powder coat paint
Load Cell Rated: NTEP, IP65
J-Box Construction: Mild steel

Loadcell Material: Alloy tool steel potted

Loadcell Rated Output: 3 mv/V

Loadcell Output Resistance: 350 ohm

J-Box Access: Top access for easy installation and service Leveling Feet: Four top access holes for quick installation Threaded Eye Bolts: Four threaded top access eye-bolt

holes for easy mobility and pit service

Corner Protection: Closed corners to prevent damage

to leveling feet while installing the scale

Overload Protection: 150% of rated capacity

End Loading: 100% of rated capacity

Operating Temperature: -10° C to 40° C / 14° F to 104° F

Accuracy: NTEP at 5000 divisions, Class III

Interface Cable Length: 4.6 m / 15' Shipping Weight: 116 kg / 225 lb Certifications: NTEP CC #11-081

Product Code:

816965005390: DSB3636-02.5 816965005246: DSB4848-05

816965005406: DSB6060-05 (actual dimension 59" x 59")

816965005413: DSB4848-10

816965005420: DSB6060-10 (actual dimension 59" x 59")

816965005666: Optional Indicator stand

816965005437: 915 mm x 915 mm / 36" x 36" ramp

816965005468: 1220 mm x 1220 mm / 48" x 48"; 5/10K ramp

816965005451: 1500 mm x 1500 mm /

 $60"~x~48";~5/10K~ramp~\mbox{(actual dimension 59" x 48")}$

816965005482: 915 mm x 915 mm / 36" x 36" pit frame

816965005512: 1220 mm x 1220 mm / 48" x 48"; 5/10K pit frame

816965005529: 1500 mm x 1500 mm /

60" x 60"; 5/10K pit frame (actual dimension 59" x 59")

*816965005697: SBI-505 2.5 kg/5K kit *816965005703: SBI-505 5kg/10K kit

*Kits include: indicator, four load cells, interface cable and hardware

SBI-505 Specifications

Construction: Mild steel with stainless steel desk stand

or wall mount stand

Dimensions: 47 mm (W) x 220 mm (L) x 149 mm (H)

1.875" W x 8.675" L x 5.875" H

Finish: Powder coat paint

Rated: IP65

Load Cell Capability: 6 @ 350 ohm

Excitation: 5 VDC Internal ADC: 2,000,000

Display Resolution: Up to 30,000

Display: Six digit 20 mm / 0.8" high red LED

Annunciators: -0-, motion, Gross, Net, tared, Total, pcs, lb,

kg, Lo, OK, Hi

RS-232: Female DB9 connection **Time and Date:** Military format

Operator Keys: On/Off, Total, Count, kg/lb, Gross, Tare,

Zero, Print

Operating Temperature: -10° C to 40° C /14° F to 104° F

Power: 120/220VAC; Output: 9.0V center positive

Calibration: Front panel accessible

Accuracy: NTEP at 5,000 divisions, Class III

Shipping Weight: 1.3 kg / 2.875 lb Certifications: NTEP CC #11-082 Product Code: AWT05-505729

*Warranty: Includes three year parts only from time of

purchase. Consult factory.

Options:

AWT05-505962: EU mains AWT05-505961: UK mains



a division of Avery Weigh-Tronix, LLC

Brecknell

1000 Armstrong Dr., Fairmont, MN 56031 Toll free: 800-637-0529, Tel: 507-238-8702 Fax: 507-238-8271

e-mail: sales@brecknellscales.com www.brecknellscales.com



Brecknell

Foundry Lane, Smethwick West Midlands B66 2LP UK Tel: +44 (0) 845 246 6717 Fax: +44 (0) 845 246 6718 Email: sales@brecknellscales.co.uk www.brecknellscales.co.uk



