


DSB Series

Floor Scale Systems CE



- **Accuracy**– NTEP at 5000 divisions, Class III
- **Capacity**–
1250 kg x 0.2 kg / 2500 lb x 0.5 lb
2500 kg x 0.5 kg / 5000 lb x 1 lb
5000 kg x 1 kg / 10,000 lb x 2 lb
- **Construction**– Mild steel with thick safety tread top plate with heavy duty welded wide channel supports. Powder coat paint finish. Heavy-duty alloy aluminum housing indicator.
- **Power**– 9V 600mA power supply with USA/UK/EU adapters (included) and four AAA batteries (not included)
- **Display**– 6½ digits 25 mm / 1" high, seven segment LCD with white backlight
- **Operator Keys**– Setup, Print/Func, Acc/Total, Unit/Data, Tare/Preset, Zero/On/Off

DSB Series Floor Scale Systems

DSB Specifications

Load Cell Rated: NTEP, IP67

Load Cell Material: Four alloy steel potted

Load Cell Rated Output: 3 mv/V

Load Cell Output Resistance: 350 ohm +/-3.5Ω

J-Box Construction: ABS, IP65

J-Box Access: Top access for easy installation and service

Interface Cable Length: 5 m / 16'

Swivel Leveling Feet: Four top access holes for quick installation

Threaded Eye Bolts: Four threaded top access eye-bolt holes for easy mobility and pit service

Corner Protection: Closed corners to prevent damage to leveling feet while installing the scale

Overload Protection: 150% of rated capacity

Operating Temperature:

-10° C to 40° C / 14° F to 104° F

Platform Dimension:

915 mm x 915 mm / 36" x 36"

1220 mm x 1220 mm / 48" x 48"

1500 mm x 1500 mm / 60" x 60"

Height Dimension: min 95 mm / 3.75"

max 108 mm / 4.25"

Shipping Weight:

DSB3636: 70 kg / 154 lb

DSB4848: 120 kg / 265 lb

DSB6060: 161 kg / 355 lb

Certifications: CE, WEEE, UL approved power supply

Product Code:

816965006915: DSB3636-02.5

816965006922: DSB4848-05

816965006939: DSB6060-05

816965006946: DSB4848-10

816965006953: DSB6060-10

816965005437: Ramp (915 mm x 915 mm / 36" x 36")

816965005468: Ramp (1220 mm x 1220 mm / 48" x 48"; 5/10K)

816965005451: Ramp (1500 mm x 1500 mm / 60" x 48"; 5/10K)

AWT05-507338: Floor mount plate set of four

SBI 240 Specifications

Unit: kg, g, lb, oz, lb/oz, pcs, %

Protocol: Standard NCI interfaces to most common shipping software including UPS™ Worldship Online

Load Cell Capability: Eight 350 ohm

Excitation: 5 VDC up to 55mA

Internal ADC: 16,000,000

Display Resolution: 100-100,00d primary units / 100-125,000d second unit

Connection: 250 mm / 9.8" cable fixed to indicator with connector. Additional 5 m / 16.4' pigtail cable with connector.

Communication: USB (VCP) or RS-232 supplied complete with 10' cable (nine pin to nine pin type connector, bi-directional full duplex)

Annunciators: -0-, motion, gross, net, tared, total, pcs, lb, kg, lo, ok, hi

Calibration: Front panel accessible

Battery Life: Approximately 20 hours continuous

Time and Date: Year/Month/Day

Functions: Weighing, counting, check weighing, percentage weighing and accumulation

Operating Temperature:

-10° C to 40° C / 14° F to 104° F

Indicator Dimension:

220 mm (L) x 93 mm (W) x 42 mm (H)

8" L x 4" W x 2" H

Product Weight: 1 kg / 2 lb

Shipping Weight: 1.5 kg / 3 lb

Options (not included):

Indicator Floor Stand: 816965007066

350 mm (L) x 350 mm (W) x 20 mm (H)

13.8" L x 13.8" x 0.8" H

Overall Height: 998 mm / 39.3"

Weight: 4.5 kg / 10 lb

Certifications: CE, UL approved power adapter, WEEE

Product Code: 816965006960



Brecknell

1000 Armstrong Dr., Fairmont, MN 56031
Toll free: 800-637-0529, Tel: 507-238-8702
Fax: 507-238-8271
e-mail: sales@brecknellscapes.com
www.brecknellscapes.com



Brecknell

Foundry Lane, Smethwick
West Midlands B66 2LP UK
Tel: +44 (0) 845 246 6717
Fax: +44 (0) 845 246 6718
Email: sales@brecknellscapes.co.uk
www.brecknellscapes.co.uk

