

# DCSB Floor Scale Systems

Calibrated with SBI 240 LCD Indicator



This robust DCSB Floor Scale, calibrated with SBI 240 Indicator, is the ideal weighing solution for a wide variety of industries where palletized goods are constantly being weighed or moved around by pallet trucks or forklifts.

The platform deck, available in a wide range of capacities and dimensions, has 6 mm / 1/4" thick hard-wearing checker plate with powder coat surface finish and IP67 load cells.

Simple to operate, the SBI 240 indicator with LCD display offers all the functions and features needed to improve efficiency and increase productivity in most warehouses and manufacturing environments.



#### Accuracy

NTEP at 5000d, Class III, factory calibrated



#### Capacity

1250 kg x 0.2 kg / 2500 lb x 0.5 lb  
2500 kg x 0.5 kg / 5000 lb x 1 lb  
5000 kg x 1 kg / 10,000 lb x 2 lb



#### Power

9V 600mA power supply with USA/UK/EU adapters (included) and four AA batteries (not included)



#### Display

6½ digits 25 mm / 1" high, large seven segment LCD with white backlight



#### Construction

Carbon steel fabrication with 6 mm / 1/4" thick safety tread top plate & heavy duty welded channel under structure, 150% overload protection



#### Operating Keys

Setup, Print/Func, Acc/Total, Unit/Data, Tare/Preset, Zero/On/Off



#### Indicator

Comes fully calibrated with the robust aluminum SBI 240 LCD multi-function indicator

# DCSB Floor Scale Systems Calibrated with SBI 240 LCD Indicator

## SBI 240 Specifications

**Indicator Construction:** Die cast aluminum indicator housing with adjustable steel desk/wall bracket

**Display:** 6½ digits 25 mm / 1" high, large seven segment LCD with white backlight

**Operator Keys:** Setup, Print/Func, Acc/Total, Unit/Data, Tare/Preset, Zero/On/Off

**Functions:** Weighing, check weighing and accumulation

**Unit:** kg, lb

**Communication:** One USB (VCP) and one RS-232 bi-directional full duplex port

**Print Format:** Configurable

**Floor Scale Connection:** 250 mm / 9.8" cable is fixed to indicator side with quick release connector. An additional 4.5 mm / 14.76" interface cable is connected to the floor scale junction box.

**Load Cell Capability:** Up to four 350 ohm load cells

**Excitation:** 5 VDC up to 55mA

**Filtering Settings:** Adjustable

**Display Resolution:** 100-100,000d primary units / 100-125,000d second units

**Annunciators:** -0-, motion, gross, net, tare, total, lo-ok-hi, lb, kg, print

**Calibration:** Front panel accessible, multi-point

**Power:** 9V 600mA, 110-230V switch mode external power supply and comes standard with USA/UK/EU interchangeable plug adapters or four AA batteries

**Battery Life:** 32 hrs with backlight, 45 hrs without

**Operating Temperature:**

-10° C to 40° C / 14° F to 104° F

**Dimensions (L x W x H):**

241 mm x 125 mm x 64 mm / 9.5" x 4.9" x 2.5"

**Certifications:** NTEP CC #15-084 (indicator) and CC #02-070 (base), OIML R60 approved load cells, FCC, Prop 65, UL/CUL approved, UKCA, CE, RoHS 3, WEEE

## DCSB Specifications

**Deck Construction:** Fabricated from high quality mild steel with a 6 mm / ¼" hard wearing checker plate top deck structure and specially designed folded channel understructure to help maximize strength where needed

**Finish:** Powder coated surface finish

**Load Cell:** Four IP67, NTEP/OIML R60 approved, 350 Ohm ± 3.5 load cells

**Load Cell Rated Output:** 3 mV/V

**J-Box:** IP65 ABS junction box with floor scale top access for ease of installation and service

**Interface Cable Length:** 4.5 m / 14.76 ft

**Leveling Feet:** Four adjustable leveling feet with top hole access for quick installation

**Threaded Eye Bolts:** Four threaded top access eye-bolt holes for easy mobility and pit service

**Corner Protection:** Closed corner protection to prevent damage to leveling feet

**Overload Protection:** 150% of rated capacity

### Capacity and Resolution:

Model	Capacity	Dimension (in)	Dimension (mm)
DCSB3636-2.5	2500 lb x 0.5 lb 1250 kg x 0.2 kg	36 x 36 x 3.1	915 x 915 x 79
DCSB4848-05	5000 lb x 1 lb 2500 kg x 0.5 kg	48 x 48 x 3.1	1220 x 1220 x 79
DCSB5959-05	5000 lb x 1 lb 2500 kg x 0.5 kg	59 x 59 x 3.1	1500 x 1500 x 79
DCSB4848-10	10,000 lb x 2 lb 5000 kg x 1 kg	48 x 48 x 3.1	1220 x 1220 x 79
DCSB5959-10	10,000 lb x 2 lb 5000 kg x 1 kg	59 x 59 x 3.1	1500 x 1500 x 79

### Floor Scale Height Adjustment:

min 79 mm / 3.1"; max 104 mm / 4.1"

### Shipping Weight with Indicator:

DCSB3636: 70 kg / 154 lb

DCSB4848: 120 kg / 265 lb

DCSB5959: 161 kg / 355 lb

**Options:** End ramps, floor mount plates, SBI 240 floor stand, RS-232 and USB cables

 **Brecknell**

[www.brecknellscales.com](http://www.brecknellscales.com)

[www.brecknellscales.co.uk](http://www.brecknellscales.co.uk)

Part of Avery Weigh-Tronix



Brecknell is part of Avery Weigh-Tronix. Avery Weigh-Tronix is a trademark of Illinois Tool Works group of companies whose ultimate parent company is Illinois Tool Works Inc ("Illinois Tool Works"). Copyright © 2022 Illinois Tool Works. All rights reserved. This publication is issued to provide outline information only and may not be regarded as a representation relating to the products or services concerned. This publication was correct at the time of going to print, however Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service at any time.

DCSBSystemSBI240\_RoW\_L\_100103.indd  
V1 AWT35-100103